## TACS-M™

Rev. 21 Jan 2013

## Thermal Acquisition Clip-On System, Miniature TACS-M shown here on a MUM-14.



Field of View	Boresight Accuracy	Magnification	F Number
20° circular (centered)	3 MOA	1X, optical unity	1.2
Sensor	Spectral Response	Pitch	ΝΕΔΤ
320 x 240 VOx uncooled LWIR microbolometer	8-12μm	25μm	50mK
Display Brightness	Polarity	Calibration	Display
Adjustable	White hot/black hot	Manual	Kopin (RED)
Range (Clear)	Range (Obscured)	Compatibility	Interface
Detection: 300m Recognition: 260m	Detection: 250m Recognition: 210m	PVS-7, PVS-14, PVS-15, PVS-18, PVS-23, MUM-14	Standard quick connect
Battery Type	Battery Life	Dimensions	Weight
CR123, 3V Lithium, 1ea.	>3.0 hrs (23°C) 2.5 hrs (0°C)	(W x H x L) 38 x 64 x 89mm	166g with battery

\*Specifications are subject to change without notice.

Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State, Directorate of Defense Trade Controls as proscribed in the International Traffic in Arms Regulations (ITAR), Title 22 Code of Federal Regulation, Parts 120-130.

DISTRIBUTION: OSR 11-S-1578 Approved for public release; distribution unlimited. © 2011 Nivisys

## **DESCRIPTION**

The Miniature Thermal Acquisition Clip-On System (TACS-M) provides the soldier with ultimate performance in technology. Low power consumption, optimal sensor technology, and high-performance optics all seamlessly integrate to provide state of the art long wave infrared (LWIR) technology.

When added to a standard image intensified system, TACS-M provides a second channel with LWIR capability, extending engagement capabilities through obscurants. The TACS-M unit along with Nivisys experience and expertise provides the best value solution for adding low light and no light performance to currently fielded night vision systems.

The unit's waterproof and rugged construction stands up to the harshest environments and features a red display for visual security. This multi-purpose surveillance tool uses the latest in miniature thermal sensor technology and a high resolution display to provide superior imagery in the smallest package available.

For more information on the TACS-M or other Nivisys products call (480) 970-3222 or visit us on the web at www.nivisys.com.