



TAM-14™

Thermal Acquisition Monocular



Nivisys currently features the TAM-14 Thermal Monocular system designed to meet the needs of the individual user for ground based night operations. The system has set the pace for future hand held thermal devices that are head or helmet mountable as well as weapon mountable while using standard 3 volt Lithium batteries. Controls are conveniently located for right or left handed operation.

The TAM-14 is a multi-purpose system using the latest in miniature thermal sensor technology combined with the new organic light emitting diode (OLED) display to provide a superior stable image in the smallest package available.

The system was designed to maximize versatility by quickly adapting to weapons, head gear, helmets, video output and more. Incorporating in-service head and helmet mounts designed for the PVS-7 and PVS-14, the TAM-14 is compact, lightweight and intuitive to operate.

Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State, Directorate of Defense Trade Controls as proscribed in the International Traffic in Arms Regulations (ITAR), Title 22 Code of Federal Regulation, Parts 120-130.

DISTRIBUTION: Approved by DoD/OSR for public release; distribution unlimited. Copyright © April 19, 2010.

GSA★ Advantage! on-line shopping
www.gsaAdvantage.GOV Contract GS-07F-6054P

Nivisys Industries, L.L.C. • 400 S. Clark Drive, Suite 105 • Tempe, Arizona USA • 480.970.3222 • 480.970.3555(fax) • email: info@nivisys.com

Rev. 20 MAY 11

FEATURES*

- Light Weight
- Rugged Design
- Extended Battery Life
- High MTBF
- Quick-Rail Design
- Head, Helmet or Weapon Mounting Options
- One Year Warranty
- Intuitive Operation
- Video Out
- Battery "Hot Swap"
- Selection of 5 Reticles
- Direct Button Functions
 - 2x Digital Zoom
 - Polarity
 - Display Brightness
- Menu Functions
 - Reticle Select
 - Azimuth Adjust
 - Elevation Adjust

For more information on the TAM-14 or other Nivisys products call (480) 970-3222 or visit us on the web at www.nivisys.com.

Made in USA
www.nivisys.com

TAM-14 BASIC KIT:

- TAM-14 Assembly
- Soft Carry Case
- CR123 Batteries (2ea.)
- Lanyard
- Objective Lens Cap
- Cleaning Kit
- Demist Shield
- Shoulder Strap
- Eyecup
- Video Out Port
- Operator Manual (not shown)
- Quick Reference Guide (not shown)



OPTIONS



3x Lens
 For longer range observation or dedicated weapon system.



Shuttered Eyecup
 For covert operations.



Weapon Base Mount
 Detachable weapon mount.



Head/Helmet Mount Interface
 For helmet and head mount in proper orientation.



3' Video Output Cable
 For recorder interface or remote display.



TLAM
 Clip on visible and near IR lasers.



Helmet Mount
 Standard U.S. Military flip-up type helmet mount (PASGT, MICH, ACH).



Head Mount
 Allows for hands free operation without the use of a helmet (AN/PVS-7, AN/PVS-14).

SPECIFICATIONS*

Sensor

160 x 120 Amorphous Silicon Microbolometer 2D Interpolated to 320 x 240

Type

Uncooled 30 hz

Thermal Sensitivity

<80mK

Spectral Response

7 – 14 μm

Objective

25mm or 16mm

Polarity

white hot / black hot

Field of View

11 x 8.5 degrees or
 17 x 12.75 degrees

Battery Type/ Life

2 each DL123A 3v Lithium
 Over 4.5 hours continuous

Weight

483 grams (with batteries)

Dimensions

14.5cm x 7.9cm x 5.3cm

Display

OLED - 640x480 format

Diopter Range

+2 to -6

Eye Relief

27mm

Video Output

NTSC Composite Video

*Information is subject to change without notice.

